



6. KEY TO ABBREVIATIONS:
- CLG = COOLING
- HTG = HEATING
- ID = INSIDE DIAMETER
- OD = OUTSIDE DIAMETER
- OHC = OVERHEAT CUTOUT RESET BUTTON
(REQUIRED ON ELECTRIC HEAT UNITS
ONLY).

					ACCESS REQUIREMENTS	Ø 197 SPIGOTS		
UNIT	WEIGHT kg	A	B	C	D	S SPIGOT PITCH (TYP.)	TOTAL No. OFF INCLUDING SIDES	SPIGOT POSITIONS REGARDLESS OF HANDING FOR SCHEDULE PURPOSES NTS.
04/1	50	565	530	503	1150	250	4	
06/1	62	715	680	653	1300	350	4	
08/1	76	915	880	853	1500	350	4	
08/2	83	915	880	853	1500	350	4	
10/1	90	1115	1080	1053	1700	350	5	
10/2	97	1115	1080	1053	1700	350	5	
12/2	111	1315	1280	1253	1900	350	5	
14/2	126	1515	1480	1453	2100	350	6	
14/3	126	1515	1480	1453	2100	350	6	
16/2	139	1715	1680	1653	2300	350	6	
16/3	139	1715	1680	1653	2300	350	6	
18/3	152	1915	1880	1853	2500	350	7	
18/4	164	1915	1880	1853	2500	350	7	

[illegible]